

Analysis of Technical Indicators of the “4k” Channel in The Karaulbazar District

Hikmatov F

Intern-teacher of the Institute of Natural Resources Management of Bukhara NRU “TIAME”

Abduvohitov Salohiddin Samandar O’g’li

Master of the Institute of Natural Resources Management of Bukhara NRU “TIAME”

Annotation. This article provides information on the technical indicators of the 4K channel, which is located in the guard farm District of the Bukhara region. A study of the technical condition of the channel revealed deficiencies and provided a summary and suggestions for eliminating existing deficiencies and improving the technical condition.

Keywords. Channel, concrete coating, filtration immersion.

3-K channel is located in Qarovulbazar district of Bukhara region. It was commissioned in 1983. 3k channel supplies water to the lands of Qarovulbazar and Vobkent districts. Water is supplied from the KBMK channel through the Garkovul Bazar pumping station. The maximum capacity of the canal (in the main part) is 6 m³/s. The total length of the channel is 6.4 km. The upper part of the channel is 10 m wide and 2.3 m deep. The bottom of the channel is 2 m wide, the channel bed is made of concrete coating, and the slope is 2 m. The thickness of the concrete coating is 10 cm, and a waterproof film is laid over the coating. The water depth in the channel is 2 m. normal depth is 1.7 m, minimum depth is 0.6 m. The slope of the channel is 0.0005. The canal is mainly excavated from depth. Irrigated area: 1184 ha. Balance value: 110229518 sums. As a result of many years of use, in some places of the channel, the concrete coating has moved, the anti-filtration films have torn, and water has formed funnels and is flowing underground. As a result of some parts being muddy, the ability to pass water has decreased. Therefore, repairs are required to prevent water loss.

The 29.2 km length of the canal needs to be de-cluttered by machinery. 53.8 million soums are required for this. Also, 18.0 million soums are required for the repair and operation of 12 structures in need of repair, and 1.7 million soums for the restoration of 5 hydroposts. The estimated cost of the total construction and maintenance works is 73.5 million soums

3K for repairing the dam of the channel.

3K channel was commissioned in 1983. 3K channel is located in Qarovulbazar district. It supplies water to Qarovulbazar district. The total length of the canal is 6.4 km. During many years of use, parts of the canal embankment were eroded, cracks appeared in the concrete coating and became unusable. Therefore, there is a need to build anti-erosion measures and make monolithic concrete.

- The maximum capacity of the canal (in the main part) : 6 m³/s
- Concrete pavement: 6.4 km
- The soil is fertile: no
- Irrigated area: 1184 hectares.
- Balance value: soum

Technical Specifications:

1. Estimated value of completed works - 13.6 mln. Sums
2. Earthworks carried out by mechanisms - m. m³
3. The section to be repaired is 0.9 km long.
4. Monolithic concrete M- 150 -65.0 m³

Reference.

1. A Krutov, B Norkulov, P Nurmatov, M Mirzaev, “Applicability of zero-dimensional equations to forecast nonconservative components concentration in water bodies” IOP Conference Series: Materials Science and Engineering 2020 , volume 883 <https://iopscience.iop.org/issue/1757-899X/883/1>

2. B Uralov, K Isabaev, F Jamolov, M Akhmadi, M Mirzaev. "The influence of the shape the living section of the pressureless machine channel and the roughness of its wetted surface on the hydraulic resistance" International Scientific Conference Construction Mechanics, Hydraulics and Water Resources Engineering (CONMECHYDRO – 2020) 23-25 April 2020, Tashkent Institute of Irrigation and Agricultural Mechanization Engineers, Tashkent, Uzbekistan <https://iopscience.iop.org/issue/1757-899X/883/1>
3. IA Ibragimov, UA Juraev, DI Inomov. Hydromorphological dependences of the meandering riverbed forms in the lower course of the Amudarya river. IOP Conference Series: Earth and Environmental Science. (2022-01-18, Volume: 949, 1-8 p.) <https://iopscience.iop.org/article/10.1088/1755-1315/949/1/012090>
4. H Ismagilov, I Ibragimov. Hydraulic parameters on the curvilinear section of the river channel in conditions of regulated water flow. Conferința "Cadastru și Drept" Lucrări științifice, Chișinău, Moldova. (2013. Volume: 33, 69-72 б.) https://ibn.idsi.md/sites/default/files/imag_file/69-72_5.pdf
5. X.A Исмагилов, И.А. Ибрагимов. Рекомендации по гидравлическому расчету и креплению берегов русла реки Амударья, в условиях зарегулированного стока воды. Журнал: Проблемы механики. (2014/3. №1. 66-69 с.) https://scholar.google.com/citations?view_op=view_citation&hl=ru&user=B0DZEakAAAAJ&citation_for_view=B0DZEakAAAAJ:xtRiw3GOFMkC
6. XA Исмагилов, ИА Ибрагимов. Движение паводковых вод в руслах в условиях зарегулированного стока воды. Журнал: Проблемы механики. (2014. №1. 69-71 с.) https://scholar.google.com/citations?view_op=view_citation&hl=ru&user=B0DZEakAAAAJ&citation_for_view=B0DZEakAAAAJ:tS2w5q8j5-wC
7. ИА Ибрагимов. Морфологические параметры на криволинейном участке реки в условиях зарегулированного стока воды. Журнал: Проблемы механики. (2014. №1. 65-68 с.) https://scholar.google.com/citations?viewop=view_citation&hl=ru&user=B0DZEakAAAAJ&citation_for_view=B0DZEakAAAAJ:maZDTaKrznsC
8. XA Исмагилов, ИА Ибрагимов. К вопросу о коэффициенте шероховатости русел рек в условиях зарегулированного стока воды. Журнал: ГИДРОТЕХНИКА. (2013. №4. 40-45 с.) https://scholar.google.com/citations?view_op=view_citation&hl=ru&user=B0DZEakAAAAJ&citation_for_view=B0DZEakAAAAJ:1sJd4Hv_s6UC
9. Isayev S. X., Qodirov Z. Z., Oripov I. O., & Bobirova M. B. (2022). EFFECTS OF RESOURCEEFFICIENT IRRIGATION TECHNOLOGIES IN IRRIGATION OF SUNFLOWERS ON LAND HYDROGEOLOGICAL CONDITIONS. British Journal of Global Ecology and Sustainable Development, 4, 95–100. Retrieved from <https://journalzone.org/index.php/bjgesd/article/view/55>
10. Egamberdiyev, M. S., Oripov, I. U., Hakimov, S., Akmalov, M. G., Gadoyev, A. U., & Asadov, H. B. (2022). Hydrolysis during hydration of anhydrous calcium sulfosilicate. Eurasian Journal of Engineering and Technology, 4, 76-81.
11. Egamberdiev, M. S., Oripov, I. U., & Sh, T. S. (2022). Development of a Method for Measuring the Layered Moisture State of Concrete and Various Bases. Eurasian Journal of Engineering and Technology, 4, 82-84.
12. Qodirov, Z. Z., Oripov, I. A., Tagiyev, A., Shomurodova, G., & Bobirova, M. (2022). WATERSAVING IRRIGATION TECHNOLOGIES IN SOYBEAN IRRIGATION, EFFECT OF SOYBEAN ON GROWTH AND DEVELOPMENT. European Journal of Interdisciplinary Research and Development, 3, 79-84.
13. Qodirov, Z. Z., Oripov, I. O., & Sh, A. (2022). Effect of Drip Irrigation of Sunflower Crop on Soil Meliorative Status. Texas Journal of Agriculture and Biological Sciences, 8, 107-111.
14. Khodirov Z, Jumaev J, & Oripov I. (2023). Application of water-saving irrigation technologies in the irrigation of fodder beets grown as the main crop. Texas Journal of Agriculture and Biological Sciences, 17, 34–39. Retrieved from <https://zienjournals.com/index.php/tjabs/article/view/4137>